

## Contemporary mains powered infrared tap



### Product details

<b>Warranty:</b>	5 years
<b>Max rated load:</b>	n/a
<b>Doc M compliant:</b>	Yes
<b>Suitable for wet areas:</b>	Yes

### Features

- Complies with Part M of the Building Regulations
- WRAS approved
- Must be installed with a thermostatic mixing valve for premixed water (part code: BPLTMV)
- Hygienic touch-free operation
- Shuts off when hand is removed from in front of the sensor
- Water delivery automatically stops after 90 seconds (can be adjusted)

### Finish options



Polished  
chrome



Satin  
Stainless Steel



Matt black  
RAL 9005

### Product description

Contemporary infrared tap, with fittings, mains powered, polished chrome  
 Contemporary infrared tap, with fittings, mains powered, satin stainless steel  
 Contemporary infrared tap, with fittings, mains powered, matt black (RAL 9005)

### Product code

NY03-TAPIR01-CP  
 NY03-TAPIR01-SS  
 NY03-TAPIR01-MB

### Disclaimer

NYMAS Group makes every effort to ensure that the information provided on this data sheet is correct. However, we cannot guarantee this, and accept no liability for any information or advice given on this data sheet.

## Specification

Operating voltage:	9V DC
Mains supply:	230V AC 50Hz
Maximum dynamic pressure:	0.5 bar MIN, 8 bar MAX
Maximum hot water supply temperature:	70 degrees Celsius
Sensor range:	80 - 300mm (220mm preset)
Connection:	½" BSP
Flow rate:	6 litre per minute

## Dimensions (mm)

